

1	2	3	4	5	6	7	8	
ROHS							For reference only	
A								A
B								B
C								C
D								D
E								E
F								F
G								G
H								H

Pin数	尺寸A	尺寸B
1×1	-	2.54
1×2	2.54	5.08
1×3	5.08	7.62
1×4	7.62	10.16
1×5	10.16	12.70
1×6	12.70	15.24
1×7	15.24	17.78
1×8	17.78	20.32
1×9	20.32	22.86
1×10	22.86	25.40
1×11	25.40	27.94
1×12	27.94	30.48
1×13	30.48	33.02
1×14	33.02	35.56
1×15	35.56	38.10
1×16	38.10	40.64
1×17	40.64	43.18
1×18	43.18	45.72
1×19	45.72	48.26
1×20	48.26	50.80
1×21	50.80	53.34
1×22	53.34	55.88
1×23	55.88	58.42
1×24	58.42	60.96
1×25	60.96	63.50
1×26	63.50	66.04
1×27	66.04	68.58
1×28	68.58	71.12
1×29	71.12	73.66
1×30	73.66	76.20
1×31	76.20	78.74
1×32	78.74	81.28
1×33	81.28	83.82
1×34	83.82	86.36
1×35	86.36	88.90
1×36	88.90	91.44
1×37	91.44	93.98
1×38	93.98	96.52
1×39	96.52	99.06
1×40	99.06	101.60

PCB LAYOUT

Specification:

Current Rating : 3.0AMP

Temperature Range : -40℃to+105℃

Contact Resistance : 20mΩ Max

Insulation Resistance : 1000MΩ Min

Withstanding Voltage : AC 1000V

Material:

Insulator : Polyester (UL94V-0)

Standard:PBT/PA6T/LCP

Contact: Brass

Plating : Au or Sn Over 50u" Ni

Height
H=1.0mm、1.5mm、1.7mm、2.0mm、2.5mm、3.3mm

GENERAL TOLERANCES	SCALE:	NAME	DATE
LINEAR	1:1		
ANGLES			
0.0±0.25		APPROVED	
X° REF±6°			
0.00±0.15		DESIGNER	
X° ±3°			
0.000±0.08		DRAWN	
X' X'±2°			

深圳市联素连接器有限公司
SHENZHEN UNICABLE CONNECTOR CO., LTD.
公司网址WWW.SZLSTC.CN
公司邮箱SZLSTC@126.COM
公司电话0755-23765650
公司传真0755-23765753

PART. NO: LSPH-0094

DWG. NO: ENDE0094

TITLE: Pitch2.54mm Pin Header,Single Plastic, Single Row,Right Angle Type

REV: A0 SHEET: 1/1

REV.	REVISION RECORD	DATE	UNIT: MM	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN										
------	-----------------	------	----------	----------	------------	----------	-------	--	--	--	--	--	--	--	--	--	--

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---